

NAV

PREMIUM DECORATIVE SURFACES



NavlamTM
SANDBLASTED

newageveners.com.au

Navlam™ SANDBLASTED

SPECIFICATIONS

Navlam Sandblasted™ is the ultimate pre-finished timber veneer. Combining the warmth and texture of solid timber with the functionality, durability and resilience of laminate and polyurethane, Navlam Sandblasted™ is the ideal choice for any interior application. Applied horizontally or vertically*, Navlam Sandblasted™ panels deliver outstanding consistency across the grain and come in an exciting range of colours, wood grains, sandblasted textures and panel sizes. Application is limited only by the imagination.

Application

Navlam Sandblasted™ is the ideal choice for any interior application, including commercial fit-outs, wall panelling, furniture and joinery. Delivered as a pre-finished laminate sheet ready to lay on the substrate of your choice or as veneer panels finished with high quality 2-pac polyurethane, Navlam Sandblasted™ is ready for immediate fabrication or application saving you time and money.

* Navlam Sandblasted™ is suitable for vertical installations and light-use horizontal applications such as shelving. However it is not recommended for high wear horizontal surfaces such as kitchen benchtops.

The pre-finished surface contains a UV inhibitor to minimise discolouration caused by UV rays. To retain colour consistency, Navlam Sandblasted™ is not for use in areas with prolonged exposure to direct sunlight.

Fabrication

Before fabrication, check all panels for defects. Keep the plastic film on the panels during fabrication, only removing it once the product is installed.

To cut Navlam Sandblasted™, use a CNC router, panel saw or table saw. Routers for trimming edges must have a smooth, clean base plate to avoid scratching the veneer surface. When drilling into Navlam Sandblasted™, use standard wood bits, router bits or carbide-tipped bits with ball bearing guide rolls, ensuring any drill bit used is sharp. For a final edge finishing, use a flat, smooth or fine file.

Please note: the use of contact adhesive will void any warranty. Panels must only be laminated using a PUR adhesive.

Environmental Sensitivity

The timbers used to manufacture Navlam Sandblasted™ are sourced from sustainably managed forests and poplar plantations that comply with world's best practice forest management principles.

Maintenance

Once the product has been installed and all fabrication work has been completed, carefully remove the protective plastic film.

Navlam Sandblasted™ surfaces are easy to clean using a cloth dampened with warm water and detergent. If you are concerned about a particular cleaning product or detergent, check with the manufacturer for suitability. Avoid the use of abrasive cleaners (such as those containing acetone or trichloroethylene), scouring pads, steel wool and sandpaper etc., as these can damage the finish and make the surface susceptible to staining. Gently remove any dust that accumulates on the veneer surface with a soft, dry duster or microfibre cloth. When dusting, do not rub, as this action could cause the dust to become entrenched in the grain, leaving a white mark that cannot be removed. Accidental spills or splatters of a harsh material, such as ceramic cooktop cleaners, tub and tile cleaners, chlorine bleach, oven cleaners, and strong detergents should be wiped off immediately and the area cleaned thoroughly with a damp cloth. For information regarding touch-ups and repairs, please visit our website newageveneers.com.au

Edging

The Navlam Sandblasted™ collection is supplied standard with matching, highly durable 1.0mm ABS (non PVC) edging to achieve a range of edging profiles. Edging is also available in 22mm, 38mm and 54mm widths to suit a wide range of panel thicknesses.

Technical Advantages

As a reconstructed veneer, Navlam Sandblasted™ delivers consistency in woodgrain structure and tone across each panel, creating the ideal surface for large or small installations. The veneer surface is finished with high quality, scratch and stain resistant 2-pac polyurethane and laid on a laminate back. Navlam Sandblasted™ is available as a prefinished laminate sheet, ready to lay on your substrate of choice, or as a finished panel with matching ABS (non PVC) edging, making fabrication and installation simple and cost effective.

Technical Specifications

Laminate only sheet size:

2500mm x 1250mm x 1mm OR 3050mm x 1300mm x 1mm

Panel sizes:

2400mm x 1200mm OR 3000mm x 1200mm

(variable thicknesses available for both panel sizes – 16mm, 18mm, 25mm, 32mm)

Please take care to inspect all boards on delivery for any defects. A maximum bow of 10mm is acceptable in both panel sizes. Bowed boards will only be recognised under the Navlam Sandblasted™ Warranty if a full check was made prior to the boards being cut, edged and installed. Any panels that are used as doors and drawers, including any panel that exceeds 2100 x 600, must be manufactured as a Good Two Side Panel. Contact your NAV representative if any assistance is required.

Grain Direction

Navlam Sandblasted™ grain runs vertically along the length of the panel.

Exposure to Sunlight

Navlam Sandblasted™ laminates are reconstructed from natural timbers and will react to direct and indirect sunlight. The pre-finished surface contains a UV inhibitor that offers some protection against discolouration, but like all natural products, colour variation will occur over time. Excessive exposure to direct sunlight may cause timber veneers to undergo sudden and irregular colour changes.

Guarantee

New Age Veneers Pty Ltd guarantees the intrinsic qualities of Navlam Sandblasted™ laminates. Discoloration due to exposure to sunlight and ultraviolet rays cannot be considered a material defect. In the event of any dispute, the guarantee and liability of New Age Veneers Pty Ltd is limited to the replacement of any material shown to be defective. New Age Veneers Pty Ltd reserves the right to discontinue any designs or products without notice at any time.



PREMIUM DECORATIVE SURFACES