



NAVLAM™



NAVLAM SANDBLASTED - LIST PRICE - (PRICE PER M ²)				
3000 x 1200mm SHEETS (prices per sq/m excluding gst)				
EO MR MDF	18mm	20mm	27mm	34mm
G1S	\$169.80	\$170.88	\$184.94	\$195.75
G2S	\$270.38	\$277.95	\$285.52	\$296.33

LAMINATE - NOMINAL THICKNESS - LIST PRICE - (PRICE PER M ²)	
3050 x 1220mm SHEETS (prices per sq/m excluding gst)	
1mm only	
\$114.21	

EDGING - MATCHING ABS - LIST PRICE (50L/M ROLLS)		
22mm x 1.0mm	38mm x 1.0mm	54mm x 1.0mm
\$1.46 LM	\$2.16 LM	\$3.24 LM

ABS DIVERSO EDGEBOARDING - LIST PRICE - UNGLUED 50 L/M ROLLS			
Decor	22mm	38mm	54mm
Bella Noce/Brindle Oak Ply	✓ 1mm	✓ 1mm	✓ 1mm
Birch Ply	✓ 1mm	✓ 1mm	✓ 1mm
Chai/Beachwood Ply	✓ 1mm	✓ 1mm	✓ 1mm & 2mm
Lamora/Oak Ply	✓ 1mm	✓ 1mm	✓ 1mm
Melaluka/Bella Noce Ply	✓ 1mm	✓ 1mm	✓ 1mm
	\$1.46 LM	\$2.16 LM	\$3.24 LM

An edgeworking range designed to complement our existing range of products. Product Use: Edging for cabinetry/kitchen doors and solid core doors, hollow doors, bench tops, table tops. ABS Divero is ideal for use in heavy traffic areas. General maintenance: Cleaning is best achieved by using warm water and detergent. Application: Edging can be applied by using conventional hot melt edgebanders. Contact adhesive or water based adhesive can also be used. Availability: ABS Divero Edgebanding available ex-stock from New Age Veneers.

PACKAGING AND FREIGHT - Metropolitan & Interstate

Sydney Metro - \$100.00 VIC, ACT, SA, Brisbane Metro - \$119.00
 WA, Far Nth QLD, NT, TAS, Country NSW - POA
 Edging \$60.00

ABS Divero Edgebanding Packaging and Freight - Metropolitan & Interstate \$60.00
 Pricelist effective as of July, 2020 (Excluding GST)

Navlam Sandblasted™ is the ultimate pre-finished timber veneer. Combining the warmth and texture of solid timber with the functionality, durability and resilience of laminate and polyurethane, **Navlam Sandblasted™** is the ideal choice for any interior application. Applied horizontally or vertically*, **Navlam Sandblasted™** panels deliver outstanding consistency across the grain and come in an exciting range of colours, wood grains, sandblasted textures and panel sizes. Application is limited only by the imagination.

TECHNICAL & DESIGN ADVANTAGES

As a reconstructed veneer, Navlam Sandblasted™ delivers consistency in woodgrain structure and tone across each panel, creating the ideal surface for large or small installations. The veneer surface is finished with high quality, scratch and stain resistant 2-pac polyurethane and laid on a laminate back.

Navlam Sandblasted™ is available as a prefinished laminate sheet, ready to lay on your substrate of choice, or as a finished panel with matching ABS (non PVC) edging, making fabrication and installation simple and cost effective.

ENVIRONMENTAL

Navlam Sandblasted™ are an environmentally sustainable choice in pre-finished timber veneers. No matter where in the world the raw materials to manufacture the product are sourced, our stringent sustainable sourcing criteria must be met, which includes strict forest management practices and sourcing veneers from controlled origin timbers and reconstructed to optimise consistency in colour and grain.

APPLICATION

Navlam Sandblasted™ is the ideal choice for any interior application, including commercial fit-outs, wall panelling, furniture and joinery. Delivered as a pre-finished laminate sheet ready to lay on the substrate of your choice or as veneer panels finished with high quality 2-pac polyurethane, Navlam Sandblasted™ is ready for immediate fabrication or application saving you time and money.

* Navlam Sandblasted™ is suitable for vertical installations and light-use horizontal applications such as shelving. However it is not recommended for high wear horizontal surfaces such as kitchen benchtops.

The pre-finished surface contains a UV inhibitor to minimise discolouration caused by UV rays. To retain colour consistency, Navlam Sandblasted™ is not for use in areas with prolonged exposure to direct sunlight.

EDGING

The Navlam Sandblasted™ collection is supplied standard with matching, highly durable 1.0mm ABS (non PVC) edging to achieve a range of edging profiles.

Edging is also available in 22mm, 38mm and 54mm widths to suit a wide range of panel thicknesses.

GUARANTEE

New Age Veneers Pty Ltd guarantees the intrinsic qualities of Navlam Sandblasted™ laminates. Discoloration due to exposure to sunlight and ultraviolet rays cannot be considered a material defect. In the event of any dispute, the guarantee and liability of New Age Veneers Pty Ltd is limited to the replacement of any material shown to be defective. New Age Veneers Pty Ltd reserves the right to discontinue any designs or products without notice at any time.

FABRICATION

Before fabrication, check all panels for defects. Keep the plastic film on the panels during fabrication, only removing it once the product is installed.

To cut Navlam Sandblasted™, use a CNC router, panel saw or table saw. Routers for trimming edges must have a smooth, clean base plate to avoid scratching the veneer surface. When drilling into Navlam Sandblasted™, use standard wood bits, router bits or carbide-tipped bits with ball bearing guide rolls, ensuring any drill bit used is sharp. For a final edge finishing, use a flat, smooth or fine file.

Please note: the use of contact adhesive will void any warranty. Panels must only be laminated using a PUR adhesive.

CLEANING & MAINTENANCE

Navlam Sandblasted™ surfaces are easy to clean. Simply use a cloth dampened with warm water and detergent. If in doubt about a particular cleaning product or detergent, check with the manufacturer for suitability. Avoid the following when cleaning, as these substances and materials could damage the finish of your Navlam Sandblasted™ panels and make the surface susceptible to staining:

- Acetone or trichloroethylene
- Abrasive cleaners, harsh detergents and powders
- Scouring pads, steel wool and sandpaper
- Ceramic cooktop cleaners
- Bathroom and tile cleaners
- Oven cleaners
- Chlorine bleach

Accidental spills or splatters of any harsh substance should be wiped off immediately and the area cleaned thoroughly with a damp cloth.

For information regarding touch-ups and repairs, please visit our website newageveneers.com.au or call 02 9457 9622.

EXPOSURE TO SUNLIGHT

Navlam Sandblasted™ laminates are reconstructed from natural timbers and will react to direct and indirect sunlight. The pre-finished surface contains a UV inhibitor that offers some protection against discolouration, but like all natural products, colour variation will occur over time. Excessive exposure to direct sunlight may cause timber veneers to undergo sudden and irregular colour changes.

GRAIN DIRECTION

Navlam Sandblasted™ grain runs vertically along the length of the panel.

TECHNICAL SPECIFICATIONS

Laminate only sheet size: 3050mm x 1220mm x 1mm
Panel sizes: 3000mm x 1200mm
(Various thicknesses available)

Please take care to inspect all boards on delivery for any defects. Bowed boards will only be recognised under the Navlam Sandblasted™ Warranty if a full check was made prior to the boards being cut, edged and installed. NAV will not warrant any bowing issues that may occur when purchasing Navlam Sandblasted™ G1S on board.

NAVLAM™

DÉCORS	GRAIN STRUCTURE	PANEL WIDTH	PANEL LENGTH
Black Pearl	Crown	1200mm	3000mm
Euro Oak	Crown	1200mm	3000mm
European Walnut	Crown Quarter Cut	1200mm	3000mm
Mahogany Gum	Crown	1200mm	3000mm
Milan Walnut	Crown Quarter Cut	1200mm	3000mm
Smokey Oak	Crown	1200mm	3000mm
Stormed Ash	Straight Quarter Cut	1200mm	3000mm
Velvet Oak	Straight Quarter Cut	1200mm	3000mm
Wood Drift	Crown Quarter Cut	1200mm	3000mm

* For full sheet images please refer to website

* Matching ABS edging available

* When using Navlam on board for doors and drawers NAV recommends the use of G2S boards only. NAV will not warrant any bowing issues that occur when purchasing Navlam G1S on board

* Please see our website for more information.

Navlam™

NAV