



NAVENEER™



NAVENEER - LIST PRICE - (PRICE PER M²)

3000 x 1200mm SHEETS (prices per sq/m excluding gst)				
EO MR MDF	17mm	19mm	26mm	33mm
G1S BAMO	\$96.13	\$97.25	\$102.99	\$108.56
G2S	\$160.97	\$162.11	\$167.83	\$173.43

NAVENEER - LIST PRICE- VENEER ONLY (PRICE PER M²)

Veneer only	\$49.97
-------------	---------

NAVENEER EDGING - LIST PRICE (50LM ROLLS)

22mm x 0.6mm	38mm x 0.6mm
\$1.73 LM	\$3.24 LM

G1S (GOOD 1 SIDE) - BAMO
 G2S (GOOD 2 SIDES)
 BAMO - Back at Manufacturer Option
 Made to order - non refundable.
 Please note: Minimum orders may incur a surcharge.

PACKAGING AND FREIGHT - *Metropolitan & Interstate*
 Sydney Metro - \$100.00 VIC, ACT, SA, Brisbane Metro - \$119.00
 WA, Far Nth QLD, NT, TAS, Country NSW - POA
 Edgebanding Packaging and Freight - Metropolitan & Interstate \$60.00
 Pricelist effective as of February, 2022 (Excluding GST)

Naveneer™ Veneer is a reconstructed timber veneer that offers consistency in wood grain, structure and tone to achieve the warmth and texture of solid timber in a totally customisable form.

Available on an EO MR MDF substrate, **Naveneer™ Veneers** are supplied unfinished, allowing you to determine the final finish for maximum creative freedom.

TECHNICAL & DESIGN ADVANTAGES

Loved by designers for its consistency and versatility, Naveneer™ Veneers create the ideal surface for large or small installations. The veneer panels are available in a broad selection of colours & finishes, including everything from natural wood grains to bold contemporary looks. Predictability in the look and texture of the veneer is assured over conventional veneers due to Naveneer™ Veneer's manufacturing process.

Supplied unfinished with the grain running vertically along the length of the sheet, Naveneer™ Veneers let you decide on the final look you wish to achieve. The panels may be laid on your substrate of choice and our matching edging provides a professional finish to your project.

ENVIRONMENTAL

Naveneer™ Veneers are an environmentally sustainable choice in timber veneers, which includes strict forest management practices and sourcing from controlled origin timbers and reconstructed to optimise consistency in colour and grain.

APPLICATION

Designed for interior applications, Naveneer™ Veneers are perfect for residential or commercial applications, including doors, wall panelling, furniture, acoustic panelling and commercial joinery. The veneers are suitable for vertical installations and light-use horizontal applications, such as shelving. However the product is not recommended for high-wear horizontal surfaces such as kitchen benchtops and interior installations where extreme exposure to direct sunlight is an issue. Naveneer™ Veneers are available in a range of colours, grain structures and unique designs. Download the Naveneer™ Veneers Availability Chart from our website www.newageveneers.com.au to view the complete collection.

GUARANTEE

NAV guarantees the intrinsic qualities of Naveneer™ Veneers. Discolouration due to exposure to sunlight and ultraviolet rays and/or slight colour variations between different Naveneer™ Veneer panels cannot be considered a defect. In the event of any dispute, the guarantee and liability of New Age Veneers Pty Ltd is limited to the replacement of any material shown to be defective. New Age Veneers Pty Ltd reserves the right to discontinue any designs or products without notice at any time.

CLEANING & MAINTENANCE

Naveneer™ Veneer surfaces are easy to clean. Simply use a cloth dampened with warm water and detergent. If in doubt about a particular cleaning product or detergent, check with the manufacturer for suitability. Avoid the following when cleaning, as these substances and materials could damage the finish of your Naveneer™ Veneer panels and make the surface susceptible to staining:

- Acetone or trichloroethylene
- Abrasive cleaners, harsh detergents and powders
- Scouring pads, steel wool and sandpaper
- Ceramic cooktop cleaners
- Bathroom and tile cleaners
- Oven cleaners
- Chlorine bleach

Accidental spills or splatters of any harsh substance should be wiped off immediately and the area cleaned thoroughly with a damp cloth.

For information regarding touch-ups and repairs, please visit our website newageveneers.com.au or call 02 9457 9622.

COLOUR CONSISTENCY

Although Naveneer™ Veneer is a reconstructed timber veneer, it retains similar colour and grain characteristics to natural timbers. As a result, subtle grain differences may be visible between block lots. Colour variation of ±10% may also be evident between block lots due to batch dyeing. Just like natural timber, it is impossible to guarantee complete colour consistency between production blocks.

We recommend finishing panels with BC Coatings UT160UV MAX which is a 2-pac polyurethane containing both a non-yellowing agent and UV inhibitor.

A UV inhibitor offers some protection against discolouration, but like all natural products, colour variations will occur over time. Prolonged exposure to excessive sunlight may cause timber veneers to undergo sudden and irregular colour changes and is therefore not recommended.

TECHNICAL SPECIFICATIONS

Panel sizes: 3000mm x 1200mm (variable thickness options available).

Ask your local NAV representative for specifications and we will manufacture your panels to order.

G1S (veneer on front face and balancing back on reverse of board); G2S (veneer on both sides); 3000 x 1200mm G1S or G2S Naveneer™ edging in 0.6mm thickness. (available in 22mm and 38mm widths).

We recommend finishing panels with BC Coatings UT160UV MAX which is a 2-pac polyurethane containing both a non-yellowing agent and UV inhibitor.

A UV inhibitor offers some protection against discolouration, but like all natural products, colour variation will occur over time. Contact your local representative or call 02 9457 9622.

NAVENEER™

DÉCORS	GRAIN STRUCTURE	PANEL WIDTH	PANEL LENGTH
Brescia	Crown Quarter Cut	1200mm	3000mm
Classic Ebony	Rift Quarter Cut	1200mm	3000mm
Emilia	Rift Quarter Cut	1200mm	3000mm
Espresso Oak	Crown	1200mm	3000mm
Florence Oak <small>NEW</small>	Crown Quarter Cut	1200mm	3000mm
Frassino	Crown	1200mm	3000mm
Griseo Elm	Crown Quarter Cut	1200mm	3000mm
Italian Walnut <small>NEW</small>	Crown Quarter Cut	1200mm	3000mm
Lamora	Rift Quarter Cut	1200mm	3000mm
Milan Walnut	Crown Quarter Cut	1200mm	3000mm
Murray Walnut	Rift Quarter Cut	1200mm	3000mm
Noce Doumo	Crown	1200mm	2700mm
Perla Nera	Crown	1200mm	3000mm
Portofino	Rift Quarter Cut	1200mm	3000mm
Ribbon Oak	Crown	1200mm	3000mm
Sierra Fineline <small>NEW</small>	Strata	1200mm	3000mm
Sorrento	Crown Quarter Cut	1200mm	3000mm
Toscano Elm	Rift Quarter Cut	1200mm	3000mm
Umbria	Crown	1200mm	3000mm
Venezia	Crown Quarter Cut	1200mm	3000mm

* For full sheet images please refer to website

* Edging available in 22mm and 38mm - 0.6mm Thickness

* Please see our website for more information.

* Pricelist effective as of February, 2022 (Excluding GST)

Naveneer

NAV