

NAVLAM Sandblasted™

# Designer's Choice



**NAV**  
DESIGNER SURFACES™

Version Z90823

For more information

T 02 9457 9622

[reception@newageveneers.com.au](mailto:reception@newageveneers.com.au)

[newageveneers.com.au](http://newageveneers.com.au)

NAVLAM Sandblasted™ is the ultimate pre-finished reconstructed timber veneer. Combining the warmth and texture of solid timber with the functionality, durability, and resilience of a laminate with an acrylic polyurethane finish, NAVLAM Sandblasted™ is the ideal choice for any interior application. Applied vertically or low wear horizontal applications, NAVLAM Sandblasted™ panels deliver outstanding consistency across the grain and comes in an exciting range of colours, wood grains and panel sizes. Application is limited only by the imagination.

#### TECHNICAL & DESIGN ADVANTAGES

As a reconstructed veneer, NAVLAM Sandblasted™ delivers consistency in woodgrain structure and tone across each panel, creating the ideal surface for large or small installations. The veneer surface is finished with high quality, scratch and stain resistant 2-pac acrylic polyurethane finish and laid on a laminate back. NAVLAM Sandblasted™ is available as a finished panel on your E0 MR MDF substrate thickness of your choice, all décor colours have matching ABS (non-PVC) edging, making fabrication and installation simple and cost effective.

#### ENVIRONMENTAL

NAVLAM Sandblasted™ laminates and panels are an environmentally sustainable choice in pre-finished timber veneers. Our stringent sustainable sourcing criteria must be met, which includes strict forest management practices and sourcing veneers from controlled origin veneer suppliers.

#### APPLICATION

NAVLAM Sandblasted™ is the ideal choice for any interior application, including commercial fitouts, wall panelling, furniture and joinery. NAVLAM Sandblasted™ comes ready for immediate fabrication or application.

NAVLAM Sandblasted™ is suitable for vertical installations and light-use horizontal applications such as shelving. However, it is not recommended for high wear horizontal surfaces such as kitchen benchtops. The pre-finished surface contains a UV inhibitor to minimise discolouration caused by UV rays. To retain colour consistency, NAVLAM Sandblasted™ is not for use in areas with prolonged exposure to direct sunlight.

#### EDGING

The NAVLAM Sandblasted™ collection is supplied with matching, highly durable 1.0mm ABS (non-PVC) edging to achieve a range of edging profiles. Edging is also available in 22mm, 38mm and 54mm widths to suit a wide range of panel thicknesses.

#### GRAIN DIRECTION

NAVLAM Sandblasted™ grain runs vertically along the length of the panel.

#### GUARANTEE

New Age Veneers Pty Ltd guarantees the intrinsic qualities of NAVLAM Sandblasted™ laminates. Discoloration due to exposure to sunlight and ultraviolet rays cannot be considered a material defect. In the event of any dispute, the guarantee and liability of New Age Veneers Pty Ltd is limited to the replacement of any material shown to be defective. New Age Veneers Pty Ltd reserves the right to discontinue any designs or products without notice at any time.

#### FABRICATION

Before fabrication, check all panels for defects. Keep the plastic film on the panels during fabrication, only removing it once the product is installed. To cut Navlam Sandblasted™, use a CNC router, panel saw, or table saw. Routers for trimming edges must have a smooth, clean base plate to avoid scratching the veneer surface. When drilling into NAVLAM Sandblasted™, use standard wood bits, router bits or carbide-bits with ball bearing guide rolls, ensuring any drill bit used is sharp. For a final edge finishing, use a flat, smooth, or fine file. Please note: the use of contact adhesive will void any warranty. Panels must only be laminated using a PUR adhesive.

#### CLEANING & MAINTENANCE

NAVLAM Sandblasted™ surfaces are easy to clean. Simply use a cloth dampened with warm water and detergent. If in doubt about a particular cleaning product or detergent, check with the manufacturer for suitability. Avoid the following when cleaning, as these substances and materials could damage the finish of your NAVLAM Sandblasted™ panels and make the surface susceptible to staining:

- Acetone or trichloroethylene
- Abrasive cleaners, harsh detergents, and powders
- Scouring pads, steel wool and sandpaper
- Ceramic cooktop cleaners
- Bathroom and tile cleaners
- Oven cleaners
- Chlorine bleach

Accidental spills or splatters of any harsh substance should be wiped off immediately and the area cleaned thoroughly with a damp cloth.

#### EXPOSURE TO SUNLIGHT

NAVLAM Sandblasted™ laminates are reconstructed from natural timbers and will react to direct and indirect sunlight. The pre-finished surface contains a UV inhibitor that offers some protection against discolouration, but like all natural wood products, colour variation will occur over time. Excessive exposure to direct sunlight may cause timber veneers to undergo sudden and irregular colour changes.

#### TECHNICAL SPECIFICATIONS

Laminate only sheet size: 3050mm x 1220mm x 1mm Panel sizes: 3000mm x 1200mm (Various E0 MR MDF thicknesses available) Please take care to inspect all boards on delivery for any defects. Bowed boards will only be recognised under the NAVLAM Sandblasted™ Warranty if a full check was made prior to the boards being cut, edged, and installed.

NAV will not warrant any bowing issues that may occur when purchasing NAVLAM Sandblasted™ G1S on board due to unbalanced faces.

NAVLAM Sandblasted™ Decor Specifications			
DECORS	GRAIN STRUCTURE	PANEL LENGTH	PANEL WIDTH
Brescia	Crown Quarter Cut	3000mm	1200mm
Italian Oak	Crown Quarter Cut	3000mm	1200mm
Lamora	Rift Quarter Cut	3000mm	1200mm
Pienza Oak	Crown	3000mm	1200mm

NAVLAM Sandblasted™ List Price (Per M <sup>2</sup> )					3000mm x 1200mm Sheets				
EO MR MDF	18mm	20mm	27mm	34mm					
G1S	\$178.29	\$179.42	\$194.19	\$205.54					
G2S	\$283.90	\$291.85	\$299.80	\$311.15					

Laminate - Nominal Thickness List Price (Per M <sup>2</sup> )	
3050 x 1220mm Sheets	
\$119.92 - 1mm only	

NAVLAM Sandblasted™ on NAVCORE™ – Falcatta Light Weight Blockboard (Per M <sup>2</sup> ) 2980mm x 1200mm		
NAVCORE™	40mm	52mm
G1S	\$259.94	\$271.86
G2S	\$343.39	\$361.27

Matching ABS Edging (Unglued 50LM Rolls)		
22mm x 1mm	38mm x 1mm	54mm x 1mm
\$1.53 LM	\$2.27 LM	\$3.40 LM

\* For full sheet images please refer to website

\* Matching ABS edging available

\* When using NAVLAM on board for doors and drawers NAV recommends the use of G2S boards only. NAV will not warrant any bowing issues that occur when purchasing Navlam G1S on board.

ABS Diverso™ Edging List Price (Unglued 50LM Rolls)			
Decor	22mm	38mm	54mm
Bella Noce/Brindle Oak Ply	1mm	1mm	1mm
Birch Ply	1mm	1mm	1mm
Lamora/Oak Ply	1mm	1mm	1mm
Melaluka/Bella Noce Ply	1mm	1mm	1mm
	\$1.53 LM	\$2.27 LM	\$3.40 LM

An Edging range designed to complement our existing range of products. Product Use: Edging for cabinetry/kitchen doors and solid core doors, hollow doors, bench tops, table tops. ABS Diverso is ideal for use in heavy traffic areas. General maintenance: Cleaning is best achieved by using warm water and detergent. Application: Edging can be applied by using conventional hot melt edgebanders. Contact adhesive or water based adhesive can also be used.

#### Packaging and Freight

Sydney Metro \$100.00  
VIC, ACT, SA, Brisbane Metro \$119.00  
WA, Far Nth QLD, NT, TAS, Country NSW|VIC|SA|QLD – POA

#### Edging, Packaging and Freight

Metropolitan & Interstate \$60.00

#### Laminate only, Packaging and Freight

Metropolitan & Interstate \$85.00 (Excluding WA - POA).

Pricelist effective as of August 2023 (Excluding GST).

